



DIMENSION CLASSIFICATION	
SYMBOL	DESCRIPTION
▲	CRITICAL

CAT. NO.	L1	L2	L3	L4	L5	W1	W2	W3	W4	H	T	R1	R2	P
TOLERANCE	+0.2 -0.1	+0.2 -0.2	+0.2 -0.2	+0.2 -0.2	+0.2 -0.2	+0.1 -0.1	+0.2 -0.2	+0.2 -0.2	+0.2 -0.2	+0.1 -0.1	+0.2 -0.2	+0.1 -0.1	+0.1 -0.1	+0.05 -0.05
TT- 1513	3.60	5.65	6.60	12.3	3.50	2.20	4.20	5.0	6.0	3.20	0.60	1.50	0.50	8.00

CONTROLLED COPY
TTPL

NOTES:-

MATERIAL	70/30 BRASS
FINISH	TIN
THICKNESS	0.60 ^{+0.02}
HARDNESS IN VPN	120 - 140

TT-1513

TERMINAL PITCH 8.00^{+0.05}/_{-0.05}

PLATING THICKNESS:- 1.50 MICRON MIN. IN CASE OF TIN PLATING FOR GOOD SOLDERABILITY

02	RECT. SLOT	SHOWN	REMOVED (With all related Dimensions)	17/7/05	AM	VENU	166
02	PROFILE	--	CHANGED (With all related Dimensions)	17/7/05	AM	VENU	166
01	E	3.1	2.6	17/7/04	AM	VENU	104
01	-	ROUND HOLE	RECTANGULAR SLOT with DIMENSION	17/7/04	AM	VENU	104
REV.NO.	AL. NO.	WAS	CHANGED TO	DATE	NAME	CHD.BY.	CHD.BY.
GEN.TOL.		CAT.NO.	TAB SIZE	CABLE SIZE		ALL DIMENSIONS ARE IN MM	
0-10	± 0.10	TT-1513	2.2 x 0.6	N A			
10-30	± 0.20	DRN BY MRN	CHECKED BY SANTOSH	APPROVED_BY_DATE SUJESH	FILENAME TT-1513	DATE 28-02-04	SCALE 3:1
30-100	± 0.30	TT		SWITCH TAB-B			
100-300	± 0.50	TERMINAL TECHNOLOGIES (I) PVT. LTD.		DRAWING_NUMBER	D/TT/247R02		SHEET 1 OF 1