





DETAIL B



SECTION D–D







DETAIL A

PUSH PULL RESULT		
DESCRIPTION	AT 1ST INSERTION	AT 10TH WITHDRAWAL
PUSH LOAD MAX.	N A.	
PULL LOAD MIN.		N A.
MAX. MV. DROP	N A.	
MAX. MV. DROP		N A.

DIMENSION CLASSIFICATION	
SYMBOL	DESCRIPTION
◢	CRITICAL

CAT. NO.	L ◢	W ◢	H ◢	C	S ◢	D ◢	P ◢	H1	W1	ød1
TOLERANCE	+0.3 −0.3	+0.2 −0.2	+0.2 −0.2	+0.1 −0.3	+.05 −.05	+0.5 −0.3	+.05 −.05	+0.4 −0.2	+0.2 −0.2	+0.1 −0.1
TT– 1519	8.50	10.0	11.0	0.50	0.16	1.00	26.0	13.2	3.00	2.00

NOTES:–

MATERIAL	70/30 BRASS
FINISH	NATURAL
THICKNESS	$0.80^{+0.02}$
HARDNESS IN VPN	120 – 140

TT–1519

TERMINAL PITCH $26.00^{+0.05}_{-0.05}$

PLATING THICKNESS:– 1.50 MICRON MIN.IN CASE OF PLATING

CONTROLLED COPY
TTPL

REV.NO.	AL. NO.	WAS	CHANGED TO	DATE	NAME	CHD.BY.

GEN TOL.	
0-10	±0.10
10-30	±0.20
30-100	±0.30
100-300	±0.50

CAT.NO.	TAB SIZE	CABLE SIZE	ALL DIMENSIONS ARE IN MM
TT-1519	----------	10.0 - 16.0 mm^2	

DRN. BY	CHECKED BY	APPROVED_BY_DATE	FILENAME	DATE	SCALE
VENU	SANTOSH	SUJESH	Tt-1519	15-3-04	3:1

TERMINAL TECHNOLOGIES (I) PVT. LTD.

JOINT TERMINAL (CENTRE SPLICE)

DRAWING_NUMBER D/TT/254.R0 | SHEET 1 OF 1

ISSUE NO–1/17–10–02