




DETAIL B



SECTION D-D



DETAIL A



DESCRIPTION	AT 1ST INSERTION	AT 10TH WITHDRAWAL
PUSH LOAD MAX.	N A	
PULL LOAD MIN.		N A
MAX. MV. DROP	N A	
MAX. MV. DROP		N A

DIMENSION CLASSIFICATION	
SYMBOL	DESCRIPTION
▲	CRITICAL


CAT NO.	L	T	ØD	Ød	C1	C2	C3	I1	I2	I3	C	S	D	P	B
TOLERANCE	+0.3 -0.3	+0.2 -0.2	+0.1 -0.1	+0.1 -0.1	+0.2 -0.2	+0.3 -0.3	+0.1 -0.1	+0.2 -0.2	+0.3 -0.3	+0.1 -0.1	+0.1 -0.2	+0.4 -0.4	+0.3 -0.3	+0.05 -0.05	+0.00 -0.10
TT-1867	17.1	0.50	6.60	3.20	3.50	3.50	3.10	4.50	5.00	2.25	0.30	0.10	0.60	20.0	2.90

CONTROLLED COPY
TTPL

NOTES:-

MATERIAL	70/30 BRASS
FINISH	NATURAL
THICKNESS	0.50 ^{+0.02}
HARDNESS IN VHN	115 - 135

TT-1867



TERMINAL PITCH 20.00^{+0.05}/_{-0.05}

PLATING THICKNESS:- 1.50 MICRON MIN. IN CASE OF PLATING

TERMINAL INSERTION FORCE INTO COUPLER:- NA
TERMINAL WITHDRAWAL FORCE FROM COUPLER:- NA

REV. NO.	AL. NO.	WAS	CHANGED TO	DATE	NAME	CHD. BY.

GEN TOL.	CAT NO	TAB SIZE	CABLE SIZE	ALL DIMENSIONS ARE IN MM		
0-10 ±0.10	TT-1867	N A	0.50-1.50 mm ²	DRN BY	CHECKED BY	APPROVED_BY_DATE
10-30 ±0.20						
30-100 ±0.30						
100-300 ±0.50						

TT		RING TERMINAL	
TERMINAL TECHNOLOGIES (I) PVT. LTD.		DRAWING_NUMBER	D/TT/90/R0
		SHEET	1 OF 1

ISSUE NO-1/17-10-02